


VÁLVULAS DE BOLA PARA SOLDAR

BALL VALVES WELDED ENDS

FIG. 143



Partes y materiales Parts & materials

- 1 Cuerpo Body
AISI 316
- 2 Lateral Body connector
AISI 316
- 3 Bola Ball
AISI 316
- 4 Eje Stem
AISI 316
- 5 Asientos Seat ring
PTFE
- 6 Maneta Wrench
AISI 304

- 7 Tuerca maneta Wrench Nut
AISI 304
- 8 Arandela maneta Wrench Washer
AISI 304
- 9 Prensaestopas Gland
AISI 304
- 10 Estopada Gland packing
PTFE
- 11 Junta eje Stem thrust seal
PTFE
- 12 Tornillo Bolt
AISI 304

- 13 Tuerca Nut
AISI 304
- 14 Arandela Washer
AISI 304
- 16 Dispositivo de bloqueo Locking device
AISI 304

FIG. 143



Válvulas de Bola Paso Total de 3 piezas, para Soldar BW (ASME B16.25 & DIN 3239 part 1), 1000 WOG (PN63 hasta DN 50 y PN25 desde DN 65), desde 1/4" (DN8) a 4" (DN100). Cuerpo en Acero Inoxidable (1.4408). Bola en AISI-316, Asientos en PTFE. Dispositivo de bloqueo. Las válvulas están certificadas CE y ATEX.

Three pieces Ball Valves, Full Bore, BW ends (ASME B16.25 & DIN 3239 part 1), 1000 WOG (PN63 up to DN50 and PN25 from DN65), from 1/4" (DN8) to 4" (DN100). Stainless Steel (1.4408) Body, AISI-316 Ball and PTFE seats. Locking Device. The valves are certified CE and ATEX.





Fig. 143

Size	ØA	ØB	ØF	ØD	L1	W	H	Weight	Torque	Kv
1/4" (DN 8)	18	12	9	9	60,4	94	46	0,31	5,6	6,6
3/8" (DN 10)	19,5	13,5	11	11	60,4	94	46	0,35	5,6	6,6
1/2" (DN 15)	23	18,5	15	15	66,4	104	50	0,41	9	11,2
3/4" (DN 20)	28,8	24	21	20	80,2	113	60	0,7	11,3	21,0
1" (DN 25)	35,6	29,5	26,6	25	84,2	128	65	1,2	14,7	34,0
1 1/4" (DN 32)	45	38	34	32	103,6	156	79	2	19,2	57,0
1 1/2" (DN 40)	51	44	40,5	38	111,4	156	83	2,5	24,9	80,0
2" (DN 50)	62,5	55,5	51	50	132	194	99	3,7	45,2	150,0
2 1/2" (DN 65)	77	67	64	64	164,2	246	128	7,4	73,2	265,0
3" (DN 80)	94	82,4	80,5	76	182	246	133	12,8	128,8	415,0
4" (DN 100)	116	99	98	94	226,8	317	175	23	165,4	780,0

Dimensiones en mm, peso en kg, par en Nm y Kv en m³/h.
Dimensions in mm, weight in kg, torque in Nm and Kv in m³/h.